Cat. No. XLF100

# **Complex**®

Notes

# Section 10309 – Manufactured Electric Fireplaces

# PART 1 GENERAL

#### 1.1 SECTION INCLUDES

- A. Manufactured electric fireplaces.
- B. Accessories.

## 1.2 RELATED SECTIONS

A. Section 06100 - Rough Carpentry: Wood framed rough opening and enclosure.

## 1.3 REFERENCES

- A. UL 2021
- B. CSA C22.2 No. 46

#### 1.4 SUBMITTALS

- A. Submit under provisions of Section 01300.
- B. Product Data: Manufacturer's data sheets on each product to be used, including:
  - 1. Preparation instructions and recommendations.
    - 2. Storage and handling requirements and recommendations.
  - 3. Installation methods.
- C. Manufacturer's Certificates: Certify products meet or exceed specified requirements.
- D. Manufacturer's warranty.

## 1.5 DELIVERY, STORAGE, AND HANDLING

- A. Store products in manufacturer's unopened packaging until ready for installation.
- B. Protect materials from exposure to moisture. Do not deliver until after wet work is complete and dry.

#### 1.6 WARRANTY

A. Provide the manufacturers 5 year limited warranty on electrical components.

# PART 2 PRODUCTS

#### 2.1 ACCEPTABLE MANUFACTURERS

- A. Pre-fabricated Electric Fireplace:
  - 1. Base: Dimplex Electric Fireplace Dimplex North America 1367 Industrial Road Cambridge ON N3H 4C3 1-888-DIMPLEX www.dimplex.com archdesign@dimplex.com

**Complex**®

Cat. No. XLF100

Notes

# Section 10309 – Manufactured Electric Fireplaces

- 2. Substitutions not permitted
- 3. Requests for substitutions will be considered in accordance with provisions of Section 01600.

#### 2.2 ELECTRIC FIREPLACES

- A. General:
  - 1. Provide all components and accessories required for a complete, functional unit.
  - 2. UL or CSA listed.
- B. Pre-fabricated Electric Fireplace:
  - 1. Base Product:
    - a) Dimplex Linear Electric Fireplace
    - b) Model Number: XLF100
  - 2. Description: Realistic 100" wall-mounted linear electric fireplace
  - 3. Dimensions:
    - a) Width: 100-1/4" / 2547mm
    - b) Height: 15-5/8" / 398mm
    - c) Depth: 5-7/8" / 148mm
  - 4. Framing Dimensions:
    - a) Width: 100-5/8" / 2556mm
    - b) Height: 16" / 460mm
    - c) Depth: 5-7/8" / 149mm
  - 5. Electrical:
    - a) Volts: 120 / 240
    - b) Watts: 1,500 / 2,500
    - c) BTUs: 5,118 / 8,530
    - d) Amps: 12.5 / 10.4
  - 6. Venting: Non-venting
  - 7. Operation: Flame only, flame and heat
  - 8. Heating: Louver-less, fan-forced circulation
  - 9. Liner: Steel
  - 10. Standard features:
    - a) Flame/ember bed on/off, range of color themes
    - b) Acrylic crystal ember bed with sparkle effect
    - c) LED flame technology
    - d) Pre-set and custom color effects
    - e) On-demand ceramic heater, with heat boost and ECO-mode
    - f) Hard wire capabilities 120V, 240V
    - g) Built-in touch controls
    - h) Seamless installation and edge to edge glass
  - 11. Optional Media Bed Accessories:
    - a) Driftwood and river rock accessory package
      - (includes one large and one small piece of driftwood, with loose rocks)

**Complex**®

Cat. No. XLF100

Notes

# Section 10309 – Manufactured Electric Fireplaces

- 12. Control options:
  - a) Multi-function remote control
  - b) Built-in membrane controls (Flame on/off, heat on/off, thermostat, colour options)

# PART 3 EXECUTION

#### 3.1 INSPECTION

- A. Do not begin installation until substrates have been properly prepared.
- B. If substrate preparation is the responsibility of another installer, notify Architect of unsatisfactory preparation before proceeding.
- C. Verify proper power supply and fuel source are available.

#### 3.2 PREPARATION

- A. Clean surfaces thoroughly prior to installation.
- B. Prepare surfaces using the methods recommended by the manufacturer for achieving the best result for the substrate under the project conditions.

#### 3.3 INSTALLATION

- A. Install in accordance with manufacturer's instructions and requirements of authorities having jurisdiction.
- B. Use manufacturer's guidelines for minimum clearances to combustibles, walls, and finishes.
- C. Anchor all components firmly in position for long life under hard use.
- D. Upon completion of installation, visually inspect all exposed surfaces. Touch up scratches and abrasions with touch up paint recommended by the manufacturer; make imperfections invisible to the unaided eye from a distance of 5 feet (1.5 m).

#### 3.4 PROTECTION

- A. Protect installed products until completion of project.
- B. Touch-up, repair or replace damaged products before Substantial Completion.

#### END OF SECTION